

MIG/MAG impulse welder

CRAFT-PULSE FOCUS 300 W 0,8/1,0**Profi mit Bedienfeldklappe**

Infinitely variable, for perfect MIG/MAG welding results

Article number

1362530

Brand

Craftweld

FOCUS.ARC - Concentra-
tion of energy in the
centre of the arcSIRIUS - the intuitive and
open user interface

Power factor correction

☒ Ordering: from 1
units**Description**

- Performance increase and quality improvement through digitally controlled MIG/MAG industrial processes
- FOCUS.PULS - High performance pulse welding process for steel construction: Directionally stable with adjustable heat input; Heat input reduced by 30 %; Increase of deposition rate up to 60 %; Welding with reduced seam opening angle; Significant improvement of quality; Overweldable tackers
- POWER.PULS: Weld stainless steel faster with TIG-like seam surface; Hardly any tarnish; Adjustable heat input; Welds in TIG look with double pulse; Weld-over helpers
- POWER.ARC: high arc quality, calm, stable and high-energy arc
- ROOT: spatter-free welding process for thin sheet and root welds with very good gap bridging, safe penetration and significantly higher welding speed for drop welds
- FOCUS.ARC: Welding with short, powerful arc, safe root penetration, particularly deep penetration, safe flank penetration and reduced penetration notches.
- Increased quality through better visibility into the process, better control over the arc and fewer defects

- SIRIUS user interface with Assist function for simplified operation of complex processes, easy integration into all systems, production chains and processes via freely configurable interface with full Industry 4.0 capability
- Monitoring and setting of welding parameters e.g. via tablet or smartphone
- Intelligent, resource-saving water cooling unit: centrifugal pump with high delivery rate, energy management measures the coolant temperature and cools only when required, extending the service life of all components
- Job memory for up to 500 programs
- Robust trolley with large wheels, robust holder for gas cylinders up to 50 l and integrated crane lugs

Delivery content

- Feed rollers 1.0/1.2 mm
- Professional trolley
- Cover flap for control panel

Technical data

Dimensions and weights

Length (product) approx.	650 mm
Width/depth (product) approx.	330 mm
Height (product) approx.	820 mm
Net weight approx.	56 kg

Duty cycle

Duty cycle at I _{max} . 40°C	80 %
Current at 100% DC 40°C	280 A

Standards and certifications

Degree of protection	IP 23
Insulation class	H

Setting range

Setting range MIG/MAG	20 – 310 A
-----------------------	------------

Electrical Data

Supply voltage	400 V
Phase(s)	3 Ph
Current type	AC
Mains frequency	50 Hz

Wire feed

weldable wires steel from to	0.8 – 1.2 mm
weldable wires stainless steel from to	0.8 – 1.2 mm
weldable wires aluminium from to	1.0 – 1.2 mm
Wire feet unit	4 Rollers

Input

Power consumption MIG/MAG	11 kVA
Power factor	0.95 cos phi
Efficiency	> 85 %

Cooling

Cooling type	AF
Torch cooling	water
Capacity water reservoir	5 l

Electrical connections

Fuse (slow blowing)	32 A
Positive mains voltage tolerance	15 %
Negative mains voltage tolerance	25 %
Open circuit voltage	89 V
Power consumption in idle mode	< 50 W

Manufacturer infos

Manufacturer	Stürmer Maschinen GmbH
Address	Dr.-Robert-Pfleger-Str. 26, 96103 Hallstadt, Germany
E-Mail	info@stuermer-maschinen.de

Media informations







Display with day and night mode
Display with day and night mode



Optimization parameters
displayed transparently and graphically
dynamically



Conventional arc
Conventional arc



- FOCUS.ARC arc**
- FOCUS.ARC arc with 15 percent less heat input
 - Welding with reduced seam opening angle possible
 - Perfect for root and stick welds



Equipment

Equipment

Type of construction	compact
Volume gas cylinder max.	50 l
Mains voltage compensation	✓
FOCUS.ARC	✓
ROOT	✓
POWER.PULS	✓
POWER.ARC	✓
Process MIG/MAG	✓
Process MMA	✓
Web server	optional
Burn-in stabilizer	✓

Shipping informations

Packaging Metrics		Weights		Delivery		Other	
Length	n/a	Net	86 kg	Delivery	Carrier	DualUse	Nein
Width	n/a	Gross	90 kg	Content	1 undefined	SCIP	
Height	n/a					SVHC	Nein

Manufacturer

Stürmer Maschinen GmbH
Dr.-Robert-Pfleger-Str. 26, 96103 Hallstadt, Germany
info@stuermer-maschinen.de

Prices on this data sheet are recommended retail prices, subject to change, in €, plus VAT at the statutory rate, plus packaging, shipping, transport, unloading, assembly and, if applicable, instruction costs. Sales prices of the dealers can deviate. No liability is accepted for printing errors, mistakes or incorrect presentation. Technical and optical changes are reserved. Illustration partly with optional accessories.