

FIREWOOD PROCESSING




MAIN CATALOGUE 2026

OFFER FOR OUR CUSTOMERS WHO ARE ENTREPRENEURS AND NOT CONSUMERS

Conveyor belt

FB 4500 – Conveyor belt for time-saving transport of firewood immediately after cutting



- ▶ Variable height adjustment to the loading height of different means of transport
- ▶ Tilt adjustment from 5° to 45° via cable winch with large handwheel
- ▶ Easy and safe folding and unfolding via cable winch and wheel support
- ▶ Quick and easy assembly and dismantling. Can also be carried out by a single person



Illustration shows conveyor belt FB 4500 with rocker saw HWS 701

- › Conveying length 4.50 m
- › Lifting height up to 3.50 m, steplessly adjustable
- › Can be operated, assembled and dismantled by one person



Illustration shows conveyor belt FB 4500 in transport and storage position

Model		FB 4500
Art. no.		5964500
Technical data		
Conveyor belt width	mm	250
Conveyor length	mm	4500
Belt speed	m/s	0.8
Tilt adjustment (manual cable winch)		
Conveyor height at 5°	mm	700
Conveyor height at 45°	mm	3400
Overall length in working position 5°	mm	4800
Overall length in working position 45°	mm	3700
Overall width with working position 5°/45°	mm	1100
Total height in working position 5°	mm	2130
Total height in working position 45°	mm	3500
Motor power	kW	1.1
Electrical connection ~50 Hz	V	400
Dimensions (L x W x H) approx.	mm	2770 x 1100 x 2130
Weight approx.	kg	245

EQUIPMENT	
• Transport wheels with pneumatic tyres (Ø 400 mm)	
• Fully galvanised conveyor trough	
• Steel driver	

Accessory



Model	Travelling device for ball head coupling, drawbar with support wheel
Art. no.	5971010



Model	Travelling device for tractor towing eye, drawbar with support wheel
Art. no.	5971011