

Workstation table mobile and height-adjustable, with single scissor mechanism

- ▶ Construction made of high-quality steel profiles for extremely high stability
 - ▶ Adjust the table to the desired working height by simply operating the hydraulic unit via a foot lever – gentle lifting and lowering movement
 - ▶ Design principle with smooth-running scissor mechanism ensures that the platform can be raised and lowered absolutely parallel
 - ▶ Easy to manoeuvre thanks to four heavy-duty swivel rollers
 - ▶ Two rollers equipped with brakes
 - ▶ Different worktops can be mounted on the base frame, secure fastening with plug pins
- 



Model		HT 600
Article No.		5192600
Technical data		
Load capacity	t	0.6
Table height min.	mm	400
Table height max.	mm	1010
Platform dimensions (L x W)	mm	1900 x 740
Roller diameter	mm	125
Dimensions (L x W x H) approx.	mm	1900 x 740 x 400
Weight approx.	kg	190



- *Foot-operated hydraulics for smooth lifting and lowering movements*



- *Easy to manoeuvre thanks to four heavy-duty swivel rollers, two of which are equipped with brakes*



HT 600 LAP

Workstation table, mobile, height-adjustable, with single scissor mechanism and perforated grid plate made of beech multiplex

- Construction made of high-quality steel profiles for extremely high stability
- Including high-quality perforated grid panel 2000 x 1000 x 30 mm made of beech multiplex with 100 mm hole grid and 22 mm hole diameter
- Adjust the table to the desired working height by simply operating the hydraulic unit via a foot lever – gentle lifting and lowering movement
- Design principle with smooth-running scissor mechanism ensures that the platform can be raised and lowered absolutely parallel
- Easy to manoeuvre thanks to four heavy-duty swivel rollers
- Two rollers equipped with brakes



• Foot-operated hydraulics for smooth lifting and lowering movements



• Easy to manoeuvre thanks to four heavy-duty swivel rollers, two of which are equipped with brakes

Scope of delivery:

- Perforated grid plate 2000 x 1000 x 30 mm, beech multiplex, perforation grid 100 mm, hole diameter 22 mm

ACCESSORIES



Accessories suitable for perforated grid plate	Article no.
 Clamp ► For fixing the workpiece from above ► Adjustable up to 200 mm workpiece thickness ► 360° swivelling Scope of delivery: ► One raster bolt	5193315
 Quick release with angular gear ► Adjustment stroke 130 mm ► Pressure plate length x width 100 x 78 mm ► Can be used on perforated beech grid panel Scope of delivery: ► Two raster bolts	5193316
 Single abutment ► Can be used on perforated beech grid panel Scope of delivery: ► One raster bolt ► One securing plug	5193317
 Support rail with anti-slip surface ► For attaching to worktops Scope of delivery: ► One support rail	5193318

Figure shows 2 support rails

Model	HT 600 LAP
Article No.	5192605
Technical data	
Load capacity	t 0.6
Table height min.	mm 430
Table height max.	mm 1040
Platform (L x W)	mm 2000 x 1000
Roller diameter	mm 125
Dimensions (L x W x H) approx.	mm 2000 x 1000 x 430
Weight approx.	kg 238