

minimax

holzkraft®

WOODWORKING MACHINES



MAIN CATALOGUE 2025/26

OFFER FOR OUR CUSTOMERS WHO ARE ENTREPRENEURS AND NOT CONSUMERS

Edge bander

KAG 4

Light and handy **edge bander**, with infinitely variable temperature and feed control

- ▶ Ideal for mobile use in the workshop, at assembly sites, trade fairs, etc.
- ▶ For use with moulded parts and straight workpieces
- ▶ With digital temperature control and infinitely variable adjustment of temperature and feed rate
- ▶ For PVC and ABS edges from 0.4 to 3.0 mm thickness
- ▶ Minimum inner radius of the workpiece is 25 mm
- ▶ Quick and easy set-up
- ▶ The edges can be pre-glued for corner joints
- ▶ With hot-melt adhesive basin; glue application at up to 200°C directly onto the edge
- ▶ Short warm-up time - Very good thermal insulation
- ▶ Infinitely variable regulation of the feed speed



Model		KAG 4 SET
Article No.		5400041
Technical data		
Edge thickness	mm	0.4 - 3.0
Edge height	mm	10.0 - 65.0 mm
Feed speed	m/min	2 - 6
Glue basin capacity	ml	400
Operating temperature	°C	Level 1: 120- 200 / Stage 2: 80 - 155
Input power	W/V	855 / 230
Dimensions (L x W x H) approx.	mm	250 x 190 x 350
Weight approx.	kg	8.8