

Equipment:

- TERSA cutter block
- Anodised aluminium size sliding
- Planing fence/rip fence combination
- Eccentric clamp
- Folding stop
- Cut-to-length fence with cantilever table
- Arc milling bonnet



Very quiet



minimax c 26g TERSA

Do not forget the
saw blades
(Page 44)



Model	minimax c 26g TERSA	minimax c 30g TERSA
Article No.	5500027	5500030
Technical data		
Trimming length max.	1200 mm	1200 mm
Sliding table dimensions (L x W x H)	201 x 70 x 1140 mm	201 x 70 x 1140 mm
Saw blade diameter max.	250 mm	250 mm
Cutting height max. 90°/45°	67 mm / 40 mm	67 mm / 40 mm
Cutting width to the left of the saw blade max.	1200 mm	1200 mm
Cutting width at the rip fence	500 mm	540 mm
Inclination of the saw blade	90 - 45°	90 - 45°
Dresser		
Surface planing table dimensions (L x W)	260 x 1040 mm	300 x 1200 mm
Multifunction fence planer/saw	90 / 45°	90 / 45°
Planing shaft Ø / number of planing blades	62 mm / 3 pcs.	62 mm / 3 pcs.
Thickness		
Table dimensions (L x W)	260 x 450 mm	300 x 450 mm
Working height min./max.	3 mm / 200 mm	3 mm / 200 mm
Chip removal max.	3 mm	3 mm
Feed speed	6 m/min	6 m/min
Table router		
Effective length of spindle	75 mm	75 mm
Tool diameter max.	160 mm	160 mm
Tool diameter can be lowered max.	150 mm	180 mm
Tenoning tool diameter max.	180 mm	275 mm
Spindle speed	5000 - 7500 min ⁻¹	5000 - 7500 min ⁻¹
Spindle diameter	30 mm	30 mm
Suction port	4 x Ø 120 mm	4 x Ø 120 mm
Saw blade guard suction nozzle Ø	Ø 60 mm	Ø 60 mm
Motor power ~50 Hz / S6 - 40%	3 x 1.8 kW / 400 V	3 x 1.8 kW / 400 V
Weight approx.	240 kg	245 kg
Slot mortising device (option) Art. No.: 5510030		
Table dimensions (L x W)	380 x 207 mm	380 x 207 mm
Slot height	120 mm	120 mm
Transverse movement (drilling width)	75 mm	75 mm
Longitudinal movement (drilling depth)	85 mm	85 mm