



minimax cu 300c 23N TERSA

Equipment minimax cu 300c / cu 410c

- Planing fence/rip fence combination
- Arc milling protective cover
- TERSA cutter block
- Anodised aluminium size sliding carriage
- Safety reversible stop jaws made of aluminium
- Folding stops



**Do not forget the
saw blades**
(Page 44)



Model	minimax cu 300c 23 N	minimax cu 300c 26 N	minimax cu 410c 23 N	minimax cu 410c 26 N
Article No.	5500309	5500310	5500445	5500446
Technical data.				
Trimming length max.	2300 mm	2600 mm	2300 mm	2600 mm
Sliding carriage dimensions (L x W x H)	270 x 124 x 2310 mm	270 x 124 x 2660 mm	270 x 124 x 2310 mm	270 x 124 x 2660 mm
Saw blade diameter with scorer max.	315 mm		315 mm	
Cutting height max.at 90°/45°	102 / 79 mm		100 / 79 mm	
Cutting width to the left of the saw blade max.	2310 mm	2660 mm	2310 mm	2660 mm
Cutting width at the rip fence	820 mm		900 mm	
Saw shaft speed	4,000 min ⁻¹		4,000 min ⁻¹	
Inclination of the saw blade	90° - 45°		90° - 45°	
Dresser				
Surface planing table dimensions (L x W)	300 x 1510 mm		410 x 1810 mm	
Planing shaft speed	5,200 min ⁻¹		5,200 min ⁻¹	
Planing shaft Ø / number of planing blades	72 mm / 3 pcs.		72 mm / 3 pcs.	
Thickness				
Table dimensions (L x W)	585 x 300 mm		605 x 410 mm	
Working height min./max.	3 mm / 230 mm		3 mm / 230 mm	
Chip removal max.	4 mm		4 mm	
Feed speed	7 m/min		7 m/min	
Table router				
Effective length of spindle	100 mm		100 mm	
Tool diameter can be lowered max.	180 mm		180 mm	
Tenoning tool diameter max.	275 mm		275 mm	
Spindle speed	3500 / 7000 / 10000 min ⁻¹		3500 / 7000 / 10000 min ⁻¹	
Spindle diameter	30 mm		30 mm	
Suction port	4 x Ø 120 mm		4 x Ø 120 mm	
Saw blade guard suction nozzle Ø	Ø 60 mm		Ø 60 mm	
Motor power ~50 Hz / S6 - 40%	3 x 5 kW / 400 V		3 x 5 kW / 400 V	
Weight approx.	525 kg		560 kg	



Equipment:

- Separate saw rip fence
- Separate planing and jointing fence
- Arc milling protective cover
- 4-blade TERSA cutter block
- Anodised aluminium size sliding carriage
- Aluminium stop jaws
- Folding stops
- Material roll on the trimming frame
- Graduation at the stop
- Milling fence with quick positioning
- Trimming shoe
- Eccentric clamp
- Handle for sliding carriage
- Round bar guide on the saw fence

minimax cu 410e 27 TERSA

**Do not forget the
saw blades**
(Page 44)



Model		minimax cu 410e 27 TERSA	minimax cu 410e 33 TERSA
Article No.		5500550	5500551
Circular saw technical data			
Sizing cuts max.	mm	2600	3200
Sliding carriage dimensions (L x W x H)		2660 x 360 x 142	3260 x 360 x 142
Saw-routing table dimensions (L x W x H)	mm	1250 x 430 x 900	
Saw blade Ø with scorer max.	mm	315	
Scoring saw blade Ø	mm	100	
Cutting height max.at 90°/45°	mm	100 / 70	
Cutting width to the left of the saw blade max.	mm	3260	
Cutting width at the rip fence	mm	900	
Saw shaft speed	min ⁻¹	4000	
Planer			
Planing table dimensions (L x W)	mm	410 x 2000	
Planing cutter block speed	min ⁻¹	5200	
Cutter block Ø / number of planing blades	mm/ pc.	87 / 3	
Thickness			
Table dimensions (L x W)	mm	775 x 423	
Working height min./max.	mm	3 / 230	
Chip removal max.	mm	5	
Feed speed	m/min	6 - 12	
Table router			
Spindle inclination	°	0 to -45	
Effective length of spindle	mm	125	
Tool diameter can be lowered max.	mm	240	
Tenoning tool diameter max.	mm	275	
Spindle speed	min ⁻¹	3500/ 6000 / 8000 / 10000	
Spindle diameter	mm	30	
Suction port	mm	3 x Ø 120	
Saw blade guard suction nozzle Ø	mm	Ø 60	
Motor power ~50 Hz / S6 - 40%	kW/V	3 x 5.0 / 400	
Weight approx.	kg	857	873



minimax cu 410es

Do not forget the
saw blades
(Page 44)



Model		minimax cu 410es 26	minimax cu 410es 32
Article No.		Warehouse equipment 5500558	Warehouse equipment 5500559
Model	minimax cu 410es 23	minimax cu 410es 26	minimax cu 410es 32
Article No.	5500555	5500556	5500557
Technical data			
Sizing cuts max.	2250 mm	2600 mm	3200 mm
Saw- milling table dimensions (L x W)		1380 x 465 mm	
Saw blade Ø with scorer max.		350 mm	
Scoring saw blade Ø		120 mm	
Cutting height max.at 90°/45°		118 / 84 mm	
Cutting width to the left of the saw blade max.		3300 mm	
Cutting width at the rip fence		1000 mm	
Saw shaft speed		4200 min ⁻¹	
Inclination of the saw blade		90° - 45°	
Dresser			
Surface planing table dimensions (L x W)		410 x 2200 mm	
Planing shaft speed		5000 min ⁻¹	
Planing shaft Ø / number of planing blades		95 mm / 4 pcs.	
Thickness			
Table dimensions (L x W)		775 410 mm	
Working height min./max.		3 mm / 240 mm	
Chip removal max.		5 mm	
Feed speed		6 - 12 m/min	
Table router			
Effective length of spindle		125 mm	
Tool diameter can be lowered max.		240 mm	
Tenoning tool diameter max.		320 mm	
Spindle speed		3500 / 6000 / 8000 / 10000 min ⁻¹	
Spindle diameter		30 mm	
Suction port		3 x Ø 120 mm	
Saw blade guard suction nozzle Ø		Ø 60 mm	
Motor power ~50 Hz / S6 - 40%		3 x 5 kW / 400 V	
Scoring motor power		0.55 kW	
Weight approx.	1285 kg	1300 kg	1365 kg

Equipment **warehouse equipment:**

- Swivel arm for feed unit
- On/off switch for main and scoring saw blade on the sliding carriage
- Motorised height adjustment and swivelling of the unit
- Motor power 3 x 7 kW

Equipment:

- Separate saw rip fence
- Separate dressing and jointing fence
- Scoring unit with separate motor
- Arc milling protective cover
- 4-blade TERSA cutter block
- Anodised aluminium size sliding carriage
- Graduated grid on the trimming frame
- Aluminium stop jaws
- Folding stops
- Material roll on the trimming frame
- Milling fence with quick positioning
- Trimming shoe
- Eccentric clamp
- Handle for sliding carriage