

Brush sanding and texturing machine



Series str

Brush sanding and texturing machine. Two motorised height-adjustable units

- Designed for professional structuring and sanding work
- Motorised height adjustment of the working units with digital display
- Inlet height constant
- Units can be switched on individually
- Highly resistant rubberised conveyor belt
- Stepless feed
- Unit for saw cut optics optionally available
- **Models str l:**
With infinitely variable, inverter-controlled brush speed. Enables precise adjustment of the speed to the material and is therefore particularly suitable for sensitive materials.



str 32r



- Working units can be switched on individually



- Brushed application example



- Application example brushed and saw-cut look

Scope of delivery str 32r / str 62r:

- Steel brush 0.2 mm
- Tynex brush K60

Scope of delivery str 32l / str 62l:

- Sanding brush K120
- Sanding brush K180

Model		str 32r	str 62r	str 32l	str 62l
Article No.		5506132	5506162	5506133	5506163
Technical data					
Sanding width max.	mm	300	300	600	600
Max. workpiece height	mm	300	300	300	300
Feed speed	m/min	1 - 13	1 - 13	1 - 13	1 - 13
Suction port	mm	2 x Ø 140	2 x Ø 140	2 x Ø 140	2 x Ø 140
Brush diameter	mm	190	190	240	240
Brush rotation	min ⁻¹	1500	1500	100 - 1500	100 - 1500
Sound power level Lw	dB(A)	65	65	65	65
Feed motor power	kW	0.22	0.37	0.22	0.37
Input power ~ 50 Hz	kW	6.25 / 400	8.37 / 400	6.25 / 400	8.37 / 400
Dimensions (L x W x H) approx.	mm	1300 x 1000 x 1300	1300 x 1300 x 1550	1300 x 1000 x 1300	1300 x 1300 x 1550
Weight approx.	kg	440	710	450	730