



*WOODWORKING MACHINES
FOR THE HOME AND CRAFTSMAN*



MAIN CATALOG 2025/26

OFFER FOR OUR CUSTOMERS WHO ARE ENTREPRENEURS AND NOT CONSUMERS

15. October 2025, 8:42 am

THICKNESS PLANER SURFACE PLANER- THICKNESSER



Thickness planer

DH 330

Portable thickness planer with 330 mm planing width

- ▶ Ideal for mobile use thanks to its small, lightweight and compact design
- ▶ Robust welded steel construction with sturdy cast table top
- ▶ For processing solid wood
- ▶ Simple and precise adjustment of chip removal by means of a mechanical indicator
- ▶ Powerful motor with overcurrent protection and restart protection
- ▶ Easy height adjustment thanks to hand crank and clear scale
- ▶ Folding infeed and outfeed tables with rollers for long workpieces
- ▶ With power cord holder under the discharge table
- ▶ Integrated suction funnel Ø 58 mm
- ▶ Suction adapter to Ø 100 mm included in the scope of delivery
- ▶ Four holes Ø 10 mm in the machine base for mounting on workbenches



Mechanical display of chip removal



Space-saving design – only 640 mm long with tables folded out



Little space required with folded tables, therefore easy to stow away



Easily transportable and therefore ideal for mobile use



Height adjustment via hand crank and scale



SCOPE OF DELIVERY

- Hand crank
- Suction funnel
- Suction adapter
- 2 magnets for blade change
- Allen key

Model		DH 330
Art. no.		5904330

Technical data		
Planing width max.	mm	330
Thickening table dimensions (L x W)	mm	235 x 330
Working height	mm	152
Chip removal max.	mm	2.8
Planing shafts Ø	mm	50
Number of planing blades		2
Planing shaft speed	min ⁻¹	8,500
Feed speed	m/min	6
Suction nozzle Ø Thickness	mm	52.5
Sound pressure level L _p	dB	85
Motor power ~50 Hz	kW/V	1.5 / 230
Dimensions (L x W x H) approx.	mm	640 x 585 x 490
Weight approx.	kg	33

Accessories	Art. no.
Spare planer blade set (2 pcs.)	5915330

DH 330-2

Massive thickness planer with three strip planer blades

- ▶ Rubber infeed and outfeed roller for gentle processing
- ▶ Two feed speeds
- ▶ Maximum precision thanks to solid quadruple spindle guide of the planing unit
- ▶ Quick adjustment of the planing height by handwheel with locking steps
- ▶ Integrated display for the set chip removal rate
- ▶ Equipped with pull-out workpiece supports on both sides
- ▶ Clean working thanks to extraction nozzle with chip bag
- ▶ With lighting on the front and rear
- ▶ Two storage areas on top of the machine for storing workpieces
- ▶ Two attached carrying handles for easy transport



Application example

SCOPE OF DELIVERY

- Chip bag
- Suction adapter 60/100mm

Model		DH 330-2
Article no.		5904335

Technical data		
Planing width max.	mm	330
Thicknessing table dimensions (L x W)	mm	520 x 330
Working height, Thickness min./max.	mm	3.2 / 152
Chip removal max.	mm	3.2
Planing shaft Ø	mm	46.8
Number of planing blades		3
Planing shaft speed	min ⁻¹	9,400
Feed speed	m/min	4 / 7
Suction nozzle Ø	mm	60 / 100
Input power ~50 Hz	kW	1.8 / 230
Dimensions (L x W x H) min. approx.	mm	640 x 670 x 350
Weight approx.	kg	49.5



Maximum precision thanks to solid quadruple spindle guide of the planing unit



Quick adjustment of the planing height thanks to locking steps



Equipped with pull-out workpiece supports on both sides
With lighting on the front and rear



Clean working thanks to extraction nozzle with chip bag



Two storage areas on top of the machine for storing workpieces
Two attached carrying handles for easy transport



Accessories

Spare blade set for spiral cutterhead
(PU = 3 pcs.)

Art. no.

5915335