



*WOODWORKING MACHINES
FOR THE HOME AND CRAFTSMAN*



MAIN CATALOG 2025/26

OFFER FOR OUR CUSTOMERS WHO ARE ENTREPRENEURS AND NOT CONSUMERS

15. October 2025, 8:42 am

***CIRCULAR TABLE SAWS
CONSTRUCTION SITE
CIRCULAR SAW
SLIDING TABLE SAWS
SAW-MILLING MACHINE
COMBINATION***



FKS 255-1300

Robust and precise **sliding table saw** with swivelling saw blade

- Heavy grey cast iron work table for low-vibration work and precise, straight cuts
- Saw unit can be swivelled up to 45 degrees, adjustment via handwheel
- Cutting plane directly on the saw blade
- Table extension with extendable telescopic stop and two folding stops
- Sliding table with extension arm
- Telescopic fence 1100 - 1900 mm, with two folding fences
- Telescopic stop can be swivelled 45 degrees on both sides
- Rip fence with round bar guide and fine adjustment
- Saw blade guard with suction hose
- Aluminium rip fence on round rod guide with fine adjustment
- Standard table widening and extension make it easy to work with larger workpieces
- Large central suction connection with 100 mm diameter



Saw blade height and tilt conveniently adjustable via handwheels



SCOPE OF DELIVERY

- Trimming shoe
- Eccentric clamp
- Angle stop -45° to 45°
- Saw blade 254 x 30 x 3.0 mm Z40



Telescopic fence with a length of 1100 to 1900 mm

Model		FKS 255-1300
Art. no. (230V)	230V or 400V	5902035
Art. no. (400V)		5902036

Technical data		
Table dimensions (L x W x H)	mm	650 x 350 x 835
Sliding table dimensions (L x W)	mm	1,320 x 238
Trimming length	mm	1,250
Cutting height 90°/45° max.	mm	80 / 54
Cutting width with rip fence	mm	610
Cutting width to the left of the saw blade max.	mm	845
Saw blade diameter	mm	254
Saw blade speed	min ⁻¹	4,000
Saw blade inclination	°	90 – 45
Suction nozzle Ø	mm	100
Saw blade guard suction nozzle Ø	mm	30
Input power ~50 Hz	kW/V	2.1 / 230 2 / 400
Dimensions (L x W x H) approx.	mm	1,320 x 1,750 x 1,120
Weight approx.	kg	155

* Sound pressure level at a distance of 1m according to DIN 45635 T 13

Mitre fence



Accessories

Accessories	Art. no.
Mitre fence	5912027
Saw blade 254 x 30 x 3 mm Z40	5912026

Accessories see p. 58

Sliding table saw

FKS 315-1500 E

Robust and precise **sliding table saw** with swivelling saw blade

- Grey cast iron workbench for low-vibration work
- Saw unit can be swivelled up to 45 degrees, adjustment via handwheel with scale
- Telescopic stop can be swivelled 45° on both sides and extended
- Saw blade height adjustable via handwheel
- Cutting plane directly on the saw blade
- Standard table widening and extension make it easy to work with larger workpieces
- Large central suction connection Ø 100 mm
- Saw blade guard with 38 mm suction nozzle diameter



Handwheel for height adjustment of the saw blade



SCOPE OF DELIVERY

- Saw blade 315 x 30 x 3 mm 24 teeth
- Sliding table with extension arm
- Table extension and widening
- Trimming shoe
- Rip fence with round bar guide and fine adjustment
- Saw blade guard with suction hose



Large aluminium rip fence on round rod guide with fine adjustment

Model		FKS 315-1500 E
Art. no.		5900315

Technical data		
Table dimensions (L x W x H)	mm	760 x 350 x 870
Trimming length	mm	1,370
Cutting height 90°/45° max.	mm	100/75
Cutting width with rip fence	mm	940
Saw blade diameter	mm	315
Saw blade speed	min ⁻¹	4250
Saw blade inclination	°	90 – 45
Suction nozzle Ø	mm	100
Saw blade guard suction nozzle Ø	mm	38
Input power ~50 Hz	kW/V	3 / 400
Dimensions (L x W x H) approx.	mm	3,480 x 2,430 x 1,270
Weight approx.	kg	202



Double swivelling segment guide of the saw unit for a smooth and perfect cut

New

FKS 315-1600 B / FKS 315-2000 B / FKS 315-2600 B

Sliding table saw with scoring device as standard

- ▶ Telescopic fence that can be swivelled from -45° to +45° with finely adjustable fence flap
- ▶ Robust and precise design with sliding table
- ▶ The grey cast iron worktable enables low-vibration work
- ▶ Saw blade height adjustment via handwheel
- ▶ Saw blade tilt adjustable from 90 to 45° via handwheel with scale
- ▶ Solid cantilever table with roller and telescopic arm for maximum stability
- ▶ Mitre fence and hold-down device can be moved over the entire length of the slide
- ▶ Large aluminium rip fence on round bar guide
- ▶ Powerful drive motor for constant cutting speed, even at 100 mm cutting height
- ▶ Large work table and standard table extension for cutting widths up to 1,220 mm



Stable saw unit guarantees vibration-free and precise work



Accessories	Art. no.
Interchangeable circular saw blade KSB-WZ 315/28 for cutting to size	5263128
Scoring saw blade 100 x 20 x 3 mm Z12	5910091
Trimming and production cut circular saw blade	
• Highest quality level specifically for industrial applications on stationary machines. • Laser-cut base body, application-specific use of ultra-fine grain carbide and extremely tight manufacturing tolerances	
KSB-BF 315/48	5263148
KSB-BF 315/60	5263160

Model		FKS 315-1600 B	FKS 315-2000 B	FKS 315-2600 B
Article no.		5902041	5902042	5902043
Technical data				
Cutting width with rip fence	mm	1,220	1,220	1,220
Cutting width to the left of the saw blade max.	mm	2,430	2,430	2,430
Trimming length	mm	1,600	2,000	2,600
Saw blade inclination	°	90 – 45	90 – 45	90 – 45
Cutting height 90° / 45° max.	mm	100 / 80	100 / 80	100 / 80
Main saw blade-Ø	mm	315	315	315
Saw blade speed	min ⁻¹	4,500	4,500	4,500
Scoring saw blade Ø	mm	100	100	100
Scoring saw blade speed	min ⁻¹	8,500	8,500	8,500
Sliding table (L x W)	mm	1,600 x 270	2,000 x 270	2,600 x 270
Table dimensions (L x W x H)	mm	1,300 x 1,260 x 865	1,300 x 1,260 x 865	1,300 x 1,260 x 865
Suction nozzle Ø	mm	98	98	98
Suction nozzle Ø Saw blade guard	mm	40	40	40
Power consumption S6	kW	3.0	3.0	3.0
Output power (motor power) ~ 50 Hz	kW	2.3 / 400	2.3 / 400	2.3 / 400
Dimensions (L x W x H)	mm	4,700 x 3,850 x 1,300	5,100 x 3,850 x 1,300	5,700 x 3,850 x 1,300
Weight approx.	kg	270	275	311

Sliding table saws

FKS 315-2000 E

Robust and precise **sliding table saw** with swivelling saw blade and scoring device

- ▶ With scoring unit as standard
- ▶ Telescopic fence that can be swivelled from -45° to +45° with finely adjustable fence flap
- ▶ Robust and precise design with sliding table
- ▶ The grey cast iron worktable enables low-vibration work
- ▶ Saw blade height adjustment via handwheel
- ▶ Saw blade tilt adjustable from 0° to 45° via handwheel with scale
- ▶ Stable saw unit guarantees vibration-free and precise work
- ▶ Solid cantilever table with roller and telescopic arm for maximum stability
- ▶ Mitre fence and hold-down device can be moved over the entire length of the slide
- ▶ Powerful drive motor for constant cutting speed, even at 100 mm cutting height
- ▶ Large work table and standard table extension for cutting widths up to 1,220 mm



Large aluminium rip fence on round rod guide with fine adjustment



SCOPE OF DELIVERY

- Saw blade 315 x 30 x 3 mm 40 teeth
- Scoring saw blade 90 x 20 x 3 mm, 12 teeth
- Sliding table with extension arm
- Material roller on the extension arm
- Rip fence with round bar guide and fine adjustment
- Table extension and widening
- Folding stop
- Trimming shoe
- Eccentric clamp
- Saw blade guard with suction hose

Model		FKS 315-2000 E
Art. no.		5900317

Technical data		
Table dimensions (L x W x H)	mm	680 x 580 x 870
Trimming length	mm	2,000
Cutting height 90°/45° max.	mm	100 / 80
Cutting width with stop	mm	1,220
Saw blade Ø max.	mm	315
Scoring saw blade max.	mm	90
Saw blade inclination	°	90 – 45
Saw blade speed	min ⁻¹	4500
Scoring speed	min ⁻¹	8500
Suction nozzle Ø	mm	38 / 100
Input power ~50 Hz	kW/V	3.7 / 400
Dimensions (L x W x H) approx.	mm	4,330 x 4,155 x 1,150
Weight approx.	kg	275



Accessories	Art. no.
Interchangeable circular saw blade 28 teeth, Ø 315 mm	5263128

Accessories see p. 58

FKS 315-2600 E

Robust and precise **sliding table saw** with swivelling saw blade and scoring device

- ▶ With scoring unit as standard
- ▶ Telescopic fence that can be swivelled from -45° to +45° with finely adjustable fence flap
- ▶ Robust and precise design with sliding table
- ▶ The grey cast iron worktable enables low-vibration work
- ▶ Saw blade height adjustment via handwheel
- ▶ Saw blade tilt adjustable from 90 to 45° via handwheel with scale
- ▶ Stable saw unit guarantees vibration-free and precise work
- ▶ Solid cantilever table with roller and telescopic arm for maximum stability
- ▶ Mitre fence and hold-down device can be moved over the entire length of the slide
- ▶ Large aluminium rip fence on round rod guide with fine adjustment
- ▶ Powerful drive motor for constant cutting speed, even at 100 mm cutting height
- ▶ Large work table and standard table extension for cutting widths up to 1220 mm



Model		FKS 315-2600 E
Art. no.		5900318

Technical data		
Table dimensions (L x W x H)	mm	1,260 x 800 x 870
Trimming length	mm	2600
Cutting height 90° / 45° max.	mm	100 / 80
Cutting width with stop	mm	1220
Saw blade Ø max.	mm	315
Scoring saw blade Ø	mm	90
Saw blade inclination	°	90 - 45
Sliding carriage size	mm	2,000 x 270
Saw blade speed	min ⁻¹	4500
Scoring speed	min ⁻¹	8500
Suction nozzle Ø	mm	38 / 100
Motor power ~50 Hz	kW / V	3 / 400
Dimensions (L x W x H) approx.	mm	5,700 x 3,850 x 1,300
Weight approx.	kg	320

SCOPE OF DELIVERY:

- Saw blade 315 x 30 x 3 mm Z40
- Scoring saw blade 90 x 20 x 3 mm Z12
- Sliding table with extension arm
- Material roller on the extension arm
- Rip fence with round bar guide and fine adjustment
- Table extension and widening
- Folding stop
- Trimming shoe
- Eccentric clamp
- Saw blade guard with suctionhose

Accessories:	Art. no.
Z 28 interchangeable circular saw blade for cutting to size	5263128
Scoring saw blade 90 x 20 x 3 mm	5910090
Trimming and production cut circular saw blade:	
KSB-BF 315/48	5263148
KSB-BF 315/60	5263160