



*WOODWORKING MACHINES
FOR THE HOME AND CRAFTSMAN*



MAIN CATALOG 2025/26

OFFER FOR OUR CUSTOMERS WHO ARE ENTREPRENEURS AND NOT CONSUMERS

15. October 2025, 8:42 am

***CIRCULAR TABLE SAWS
CONSTRUCTION SITE
CIRCULAR SAW
SLIDING TABLE SAWS
SAW-MILLING MACHINE
COMBINATION***



Circular table saws

New

TKS 256 M

Compact circular table saw for versatile applications

- ▶ Powerful 1800 W motor for a cutting height of up to 80 mm
- ▶ Easy to transport thanks to the low weight of just 20 kg
- ▶ Integrated sliding table with mitre stop and 45° blade tilt possible
- ▶ Precise adjustment of the rip fence via toothed rack for a cutting width of up to 620 mm
- ▶ Folding rip fence for workpiece support and stop for thin workpieces
- ▶ Tool-free replacement of the saw blade guard and table insert



Folding rip fence for thin workpieces



Tool-free replacement of the saw blade guard and table insert



Integrated sliding table with angle stop

SCOPE OF DELIVERY

- Saw blade 255 x 30 x 3.0 mm 48Z
- Saw bonnet
- Rip fence
- Angle stop

Model		TKS 256 M
Art. no.		5902256
Technical data		
Table dimensions (L x W x H)	mm	630 x 587 x 45
Cutting height 90°/45° max.	mm	80 / 55
Cutting width with rip fence	mm	620
Saw blade Ø	mm	255
Saw blade speed	min ⁻¹	6,000
Saw blade inclination	°	90 – 45
Suction nozzle Ø	mm	63.5
Saw blade guard suction nozzle Ø	mm	35
Input power	kW/V	1.8
Dimensions (L x W x H) approx.	mm	630 x 649 x 329
Weight approx.	kg	20



Accessories	Art. no.
Saw blade Ø 254 x 30 x 2.9 mm Z24	5267070
Saw blade Ø 254 x 30 x 2.9 mm Z48	5267075

Accessories see p. 58

TKS 316 E

Table circular saw for ripping and angular cuts

- Inclination of the saw blade from 0 to 45°, adjustable without tools
- Height adjustment of the saw blade via a handwheel and scale
- This large aluminium parallel fence features an eccentric quick-clamping mechanism and can also be used as a mitre fence
- Large, galvanised steel machine table
- Easy to move thanks to integrated chassis with two wheels and folding transport handles
- Supplied unassembled



Easy to move thanks to integrated chassis and folding transport handles

The rip fence enables ripping cuts, bevelled and angled cuts

TKS 316 E
Illustration with standard table extension, sliding table with mitre fence and chassis

SCOPE OF DELIVERY

- Chassis
- Sliding table with mitre fence
- Table widening
- Combined parallel/mitre fence
- Carbide saw blade Ø315 x 3.6 x Ø 30 mm Z24
- Saw blade guard with suction hose
- Push stick

230V
or
400V

Model		TKS 316 E	TKS 316 E
Art. no.		5902316	5902317

Technical data			
Table dimensions (L x W x H)	mm	800 x 550 x 850	
Cutting height 90°/45° max.	mm	83 / 60	
Cutting width with rip fence	mm	290	
Saw blade Ø	mm	315	
Saw blade speed	min ⁻¹	2,800	
Saw blade inclination	°	90 – 45	
Suction nozzle Ø central	mm	100	
Input power	kW/V	2.2 / 230	2.8 / 400
Dimensions (L x W x H) approx.	mm	1,600 x 600 x 1,050	
Weight approx.	kg	53	55



Easy to move thanks to chassis and foldable transport handles



Simple manual height adjustment of the saw unit using a hand crank, tilt adjustment from 0 - 45°



Ball-bearing mounted sliding table with mitre fence, infinitely adjustable from 0 to 45° with quick-clamping lever



Easy and precise adjustment of the rip fence with eccentric quick clamping using a scale



Circular table saws

TKS 316 PRO

Circular table saw for ripping and angular cuts

- Large machine table made of galvanised steel
- Standard table extension can also be fitted as a table extension on the right
- Precise saw blade tilt via handwheel with scale
- Saw blade height adjustable via easily accessible handwheel
- Precise cuts thanks to stable, double suspension of the saw unit
- Parallel stop enables rip cuts, bevel cuts and angle cuts
- Easy to move thanks to integrated chassis and folding transport handles

- High stability for precise cuts
- Precise saw blade tilting up to 45°
- Rip and mitre fence included in the scope of delivery
- Easy to transport and store



The rip fence with eccentric quick clamping can be adjusted precisely and easily using a scale.



Additional table 800 x 550 mm included in the scope of delivery Suitable for extending and widening tables



With precise and smooth height and tilt adjustment of the saw unit using easy-to-operate handwheels.



Sliding table with ball bearings Including mitre fence adjustable from -45° to +45° Fixing the stop with quick-clamping lever Mitre fence without aluminium profile, profile available as accessory



TKS 316 PRO (230 V)
Image shows Mitre fence with aluminium profile, profile and angle fence available as accessories

Appliance switch with plug and combined on/off switch

SCOPE OF DELIVERY

- Chassis
- Sliding table
- Table extension/widening , 800 x 550 mm
- Rip fence
- Carbide saw blade Ø 315 mm / 36 Z
- Saw blade guard with suction hose
- Mitre fence without aluminium profile (Profile available as an accessory)

Model		TKS 316 PRO	TKS 316 PRO
Art. no.		5902321	5902323

Technical data			
Table dimensions (L x W x H)	mm	800 x 550 x 850	
Cutting height 90°/45° max.	mm	90 / 50	
Cutting width with rip fence	mm	200	
Saw blade Ø	mm	315	
Saw blade speed	min ⁻¹	2800	
Saw blade inclination	°	90 to -45	
Suction nozzle Ø central	mm	100	
Input power ~ 50 Hz	kW	2.2 / 230	2.8 / 400
Dimensions (L x W x H) approx.	mm	1,350 x 1,250 x 1,000	
Weight approx.	kg	60	




Accessories	Art. no.
interchangeable circular saw blade for cutting to size 28 Z, Ø 315 mm	5263128
Table extension/widening, 800 x 550 mm	5912321
Aluminium profile for mitre fence	5912322

Circular table saws


TKS 200

Circular table saw with maximum cutting height 60 mm

- ▶ Large cast iron table
- ▶ Saw blade swivelling from 90° to -45° to the left, precise, accurate to the degree and conveniently adjustable via handwheel and scale
- ▶ Large central suction connection Ø 100 mm
- ▶ The stable front and rear suspension of the saw unit enables precise cuts
- ▶ The saw blade height is also adjusted via a handwheel from the operator front panel
- ▶ Equipped with a powerful motor and thermal overload protection
- ▶ Including saw blade guard with integrated suction connection
- ▶ Table extension as standard



Infinitely adjustable angle stop from -45° to 45°



Sliding table with integrated scale. Mitre fence with one folding fence and one hold-down device.



Adjustable folding fence

SCOPE OF DELIVERY

- Machine base
- Sliding table
- Rip fence
- Angle stop
- Saw blade guard with suction hose
- Table widening
- Saw blade 200 x 30 x 2.8 mm Z18

Model		TKS 200
Art. no.		5902020

Technical data		
Table dimensions (L x W x H)	mm	530 x 400 x 870
Cutting width with rip fence	mm	705
Cutting width to the left of the saw blade max.	mm	635
Saw blade Ø max.	mm	200
Cutting height 90°/-45° max.	mm	60 / 48
Saw blade inclination	°	90 – 45
Saw blade speed	min ⁻¹	4,750
Suction nozzle Ø bottom/top	mm	100 / 30
Sound pressure level LP ⁽¹⁾	dB	78.5
Motor power ~50 Hz	kW/V	1.1 / 230
Dimensions (L x W x H) approx.	mm	1,430 x 1,000 x 1,030
Weight approx.	kg	80

(1) Sound pressure level at a distance of 1m according to DIN 45635 T 13



UF 230




Accessories	Art. no.
Saw blade 200 x 30 x 2.8 mm Z18	5912020
Universal chassis UF 230	

Accessories see p. 58

TKS 254 E

Circular table saw with 45° saw blade inclination to the left

- ▶ Large cast iron table
- ▶ Stable suspension of the saw unit
- ▶ The saw blade height is adjusted via a handwheel on the operator front
- ▶ Equipped with a powerful motor and thermal overload protection
- ▶ Integrated suction connection on the saw blade guard
- ▶ Standard table extension
- ▶ Suspension of the saw unit made of sheet steel
- ▶ Saw blade inclination 45° degrees to the left



Saw blade swivelling from 90° to -45°



Sliding table with integrated scale



Rip fence with round bar guide



Angle stop not included in scope of delivery

SCOPE OF DELIVERY

- Machine base
- Sliding table
- Angle stop
- Rip fence
- Saw blade 254 x 30 x 3 mm Z40
- Saw blade guard with suction hose

Model	230V or 400V	TKS 254 E
Art. no. (230 V)		5902025
Art. no. (400 V)		5902026

Technical data		
Table dimensions (L x W x H)	mm	635 x 420 x 850
Cutting width with rip fence	mm	680
Cutting width to the left of the saw blade max.	mm	650
Saw blade Ø max.	mm	254
Cutting height 90°/-45° max.	mm	80 / 58
Saw blade inclination	°	90/-45
Saw blade speed	min ⁻¹	4,000
Suction nozzle Ø bottom/top	mm	100 / 30
Sound pressure level LP ⁽¹⁾	dB	85.1
Motor power ~50 Hz	kW/V	2.1/ 230 or 400
Dimensions (L x W x H) approx.	mm	1,430 x 1,000 x 1,030
Weight approx.	kg	105

* Sound pressure level at a distance of 1m according to DIN 45635 T 13



Accessories	Art. no.
Saw blade 254 x 30 x 3 mm Z40	5912026
Universal chassis UF 230	

Accessories see p. 58

Main catalogue 2025 | 49

Grinding

Planing

Table router

Saws

Woodturning

Extraction

Workshop equipment

Circular table saws

TKS 254 PRO

Professional circular table saw with 45° saw blade inclination to the right

- ▶ Large cast iron table
- ▶ Stable suspension of the saw unit
- ▶ The saw blade height is adjusted via a handwheel on the operator front
- ▶ Equipped with a powerful motor and thermal overload protection
- ▶ Integrated suction connection on the saw blade guard
- ▶ Standard table extension
- ▶ Cast iron saw unit suspension
- ▶ The solid construction ensures particularly high stability and vibration damping
- ▶ Saw blade inclination 45° degrees to the right



With precise and smooth height and tilt adjustment of the saw unit using easy-to-operate hand-wheels.



High-quality angle stop included in delivery



Rip fence with round bar guide



Stable saw unit guarantees vibration-free and precise work

Model	230V or 400V	TKS 254 PRO
Art. no. (230 V)		5902027
Art. no. (400 V)		5902028

Technical data		
Cutting width with rip fence	mm	610
Cutting width to the left of the saw blade max.	mm	550
Saw blade Ø max.	mm	254
Cutting height 90°/-45° max.	mm	80 / 54
Saw blade inclination	°	90 / 45
Saw blade speed	min ⁻¹	4,000
Suction nozzle Ø bottom/top	mm	100 / 30
Sound pressure level L _{PA} (1)	dB	84.2
Motor power ~50 Hz	kW/V	2.1/ 230 or 400
Dimensions (L x W x H) approx.	mm	1,430 x 1,000 x 1,030
Weight approx.	kg	131

SCOPE OF DELIVERY

- Machine base
- Sliding table
- Table extension
- Angle stop
- Rip fence
- Saw blade 254 x 30 x 3 mm Z40
- Saw blade guard with suction hose