


All the PROlift® lifting accessories are batch numbered and marked accordingly.


Manufacturing standard for the master links is EN 1677-4.

PRO-OM CRANE MASTER LINK (PEAR TYPE)



Model/ Features	WLL (t)	MBL (t)	Dimensions (mm)					Weight (kg/pc)
			A	B	R1	R2	Ø	
PRO-OM-04.00	4	20	243	155	45	50	22	2.13
PRO-OM-05.00	5	25	240	156	52	60	25	3.2
PRO-OM-05.50	5.5	27.5	275	175	45	50	25	2.78
PRO-OM-08.00	8	40	320	215	70	70	32	6.15
PRO-OM-09.00	9	45	280	175	52	60	32	5.4
PRO-OM-15.00	15	75	280	175	52	60	38	7.77
PRO-OM-20.00	20	100	320	220	70	70	45	12.7

PRO-OS MASTER LINK



Model/ Features	WLL (t)	MBL (t)	Dimensions (mm)					Weight (kg/pc)
			A	B	D	L	S	
PRO-OS-01.60	1.6	6.4	109	60	14.5	30	6.2	0.34
PRO-OS-02.12	2.12	8.48	111.5	58.5	16	31	7.5	0.54
PRO-OS-03.15	3.15	12.6	134	75	18	37	8	0.82
PRO-OS-05.30	5.3	21.2	160	88	22.5	43	11	1.5
PRO-OS-08.00	8	32	185	97	25	49.5	13	2.32
PRO-OS-11.20	11.2	44.8	200	110	32	45	19	3.95
PRO-OS-14.00	14	56	260	140	35	56.5	20	6.34
PRO-OS-17.00	17	68	307	165	40	60	22	8.96
PRO-OS-21.20	21.2	84.8	340	180	45	N/A	N/A	12.8
PRO-OS-31.50	31.5	126	350	190	50	N/A	N/A	16.55
PRO-OS-45.00	45	180	400	200	56	N/A	N/A	23.28
PRO-OS-56.00	56	224	350	200	55	N/A	N/A	20.54
PRO-OS-70.00	70	280	375	210	60	N/A	N/A	26.15
PRO-OS-90.00	90	360	450	250	70	N/A	N/A	42.45
PRO-OS-100.00	100	400	450	260	80	N/A	N/A	57.14