

DEHUMIDIFIER



Dehumidifier

Dehumidifier LEF – with timer function

- ▶ Clear LED display for user-friendly operation
- ▶ Various modes such as continuous operation, auto mode and fan function possible
- ▶ Practical 24-hour timer function
- ▶ Desired humidity can be set in stages
- ▶ Condensate container can be easily removed
- ▶ Hose connection for continuous condensate drain
- ▶ Washable carbon filter for neutralising odours
- ▶ Practical carrying handle
- ▶ Cable holder at the rear

LEF 30

- ▶ Control via Wifi possible



› Clear control panel for setting the desired mode and humidity level



Dehumidify



LEF 12

Scope of delivery:

- › 1x condensate drain hose
- › 1x filter mat with filter frame



LEF 30

Model		LEF 12	LEF 30
Art. no.		6262040	6262045
Technical data			
Refrigerant		R290	R290
Dehumidification performance [®]	l/day	12	30
Operating temperature	°C	5 – 32	5 – 32
Recommended room volume	m ³	12–15	28 – 35
Max. air volume	m ³ /h	80 – 100	230
Sound pressure level	dB(A)	43	43
Input power	W	200	600
Electrical connection	V/Hz	230	230
Dimensions (L x W x H) approx.	mm	256 x 203 x 434	338 x 247 x 511
Weight approx.	kg	9.5	16.5

Accessories	Art. no.
Filter mat incl. filter frame (LEF 12)	6263040
Filter mat incl. filter frame (LEF 30)	6263041

LEF series dehumidifier - Reliable and efficient

- ▶ Suitable for drying buildings, damp rooms, e.g. after water damage or on construction sites
- ▶ To prevent condensation and mould formation
- ▶ Mobile, impact-resistant housing for long service life
- ▶ Equipped with temperature control, defrost control, self-monitoring system, automatic hygrostat control and environmentally friendly refrigerant R290
- ▶ Control unit equipped with Smart-Touch buttons, sequence display and operating hours counter
- ▶ With removable and washable filters for use in dusty rooms
- ▶ High performance with low power consumption
- ▶ Low noise level
- ▶ With practical cable holder
- ▶ Integrated condensate pump for pumping out the condensation water via the drain hose



Including operating hours counter

LEF 51 S



Control unit equipped with Smart Touch buttons, sequence display and operating hours counter



Folding bracket for space-saving storage

Scope of delivery:
 > Condensate drain hose 5 m

Model		LEF 51 S	LEF 71 S	LEF 91 S
Art. no.		6262051	6262071	6262091
Technical data				
Refrigerant		R290	R290	R290
Dehumidification performance*	l/day	50	70	90
Operating temperature	°C	1-36	1-36	1-36
Recommended room size	m ³	80	130	170
Max. air volume	m ³ /h	600	700	850
Outlet size	mm	303 x 285	317 x 280	317 x 280
Sound pressure level	dB(A)	42	45	48
Input power	W	550	750	960
Connection voltage	V/Hz	230 /50	230 /50	230 /50
Dimensions (L x W x H) approx.	mm	550 x 500 x 700	555 x 480 x 820	555 x 480 x 820
Weight approx.	kg	36	38.5	41

*The specification refers to 30°C and 80% humidity

Accessories LEF 51 S	Article no.
Filter mat incl. filter frame	6263050
Accessories LEF 71 S & LEF 91 S	Article no.
Filter mat incl. filter frame	6263070