

New

WORK AND CONSTRUCTION SITE LIGHTS

New



LAL 400-2 DC - Foldable LED work light

- ▶ Powerful Li-ion rechargeable battery
- ▶ Flexible 230° swivel – adapts perfectly to any working position
- ▶ Integrated LED for displaying the battery status
- ▶ Three versatile SMD LED light sources for front, rear and spotlight illumination

100% Spotlight	100% Main light	50% Main light	100% Rear light
Light duration (approx. in hours)			
7:30 h	3:00 h	6:30 h	3:00 h

Technical data		LAL 400-2 DC
Art. no.		6901015

Electrical connection	V/W	3.7/5
Capacity	mAh	800
Charging time	h	2.5
Impact resistance		IK07
Dimensions (L x W x H) approx.	mm	35x20x160
Weight approx.	kg	0.09



6500 K (neutral white light)

Rechargeable battery operation | Dimmable | USB TYPE C | IP 20



▶ For hard-to-reach places

Scope of delivery:
USB-C charging cable 1 m

Accessory	Art. no.
USB-C charging cable 1 m	6909002

LAL 900 DC – Focusable LED work light

- ▶ Powerful Li-ion rechargeable battery
- ▶ Three brightness levels
- ▶ Flexible 180° swivel – adapts perfectly to any working position
- ▶ Integrated LED for displaying the battery status
- ▶ Rubberised handle for maximum grip

100%	50%	25%
Light duration (approx. in hours)		
3:30 h	7:00 h	16:00 h

Technical data		LAL 900 DC
Art. no.		6901020

Electrical connection	V/W	3.7 / 10
Capacity	mAh	2,500
Charging time	h	3
Protection class		IP54
Impact resistance		IK07
Dimensions (L x W x H) approx.	mm	46x45x205
Weight approx.	kg	0.28



6500 K (neutral white light)

Rechargeable battery operation | Dimmable | USB TYPE C | IP 54



▶ Infinitely variable focussing for a widely scattered or pinpoint beam of light

Scope of delivery:
USB-C charging cable 1 m

Accessory	Art. no.
USB-C charging cable 1 m	6909002
Spare battery	6909003

LAL 1000-2 DC - LED work light, rotatable and swivelling

- ▶ Powerful Li-ion rechargeable battery
- ▶ Two LED light sources for perfect illumination (spotlight, main light)
- ▶ Two brightness levels
- ▶ Rotates 320° for maximum flexibility
- ▶ Flexible 180° swivel – adapts perfectly to any working position
- ▶ Integrated hook on top and bottom of the device

100% Spotlight	100% Main light	50% Main light
Light duration (approx. in hours)		
11:00 h	3:00 h	6:00 h

Technical data		LAL 1000-2 DC
Art. no.		6901025

Electrical connection	V/W	3.7 / 10
Capacity	mAh	2,500
Charging time	h	3
Protection class		IP20
Impact resistance		IK07
Dimensions (L x W x H) approx.	mm	67x66x272
Weight approx.	kg	0.34



6500 K (neutral white light)

Rechargeable battery operation | Dimmable | USB TYPE C | IP 20



▶ Flexible positioning thanks to swivelling and tilting function

Scope of delivery:
USB-C charging cable 1 m

Accessory	Art. no.
USB-C charging cable 1 m	6909002

LAL 800 DC Colour – LED work light with colour temperature mode


- ▶ Powerful Li-ion rechargeable battery
- ▶ Two LED light sources for perfect illumination (spotlight, main light)
- ▶ LED for displaying the battery status
- ▶ Integrated hook on the top of the device
- ▶ Ideal conditions for precise colour matching and the detection of paint defects

	100 % spotlight	100 % main light
Light duration (approx. in hours)		
	8:00 h	4:00 h
<i>Technical data</i>		
Art. no.	LAL 800 DC Colour 6901030	
Electrical connection	V/W	3.7 / 10
Capacity	mAh	5,000
Charging time	h	6.5
Impact resistance		IK08
Dimensions (L x W x H) approx.	mm	60x35x215
Weight approx.	kg	0.39



2700 K 4500 K 6500 K

Rechargeable battery operation USB TYPE C IP 54



▶ Three colour temperature settings make it easier to detect paint defects and damage.

Scope of delivery:
1 m USB-C charging cable
Charging station

Accessory	Art. no.
USB-C charging cable 1 m	6909002

LAS 3000 DC – LED work light with power bank function

- ▶ Powerful Li-ion rechargeable battery
- ▶ Integrated power bank function with USB-A output
- ▶ Five brightness levels
- ▶ Robust aluminium housing with plastic edge protection
- ▶ Integrated LED for displaying the battery status
- ▶ Practical folding support with adjustable angle
- ▶ Device also for hanging

	100%	80%	60%	40%	20%
Light duration (approx. in hours)					
	3:00 h	4:00 h	6:00 h	12:00 h	30:00 h
<i>Technical data</i>					
Art. no.	LAS 3000 DC 6902000				
Electrical connection	V/W	7.4 / 30			
Capacity	mAh	5,000			
Charging time	h	4			
Protection class		IP65			
Impact resistance		IK08			
Dimensions (L x W x H) approx.	mm	140x55x215			
Weight approx.	kg	1.12			



6500 K (neutral white light)

Rechargeable battery operation Dimmable Powerbank function IP 54



▶ Perfect for stationary lighting at work

Scope of delivery:
USB-C charging cable 1 m

Accessory	Art. no.
USB-C charging cable 1 m	6909002

LBS 10000 AC/DC - Hybrid LED construction spotlight

- ▶ Can be used with 18V batteries thanks to battery adapter for Bosch, Makita, Milwaukee and Metabo or 230V mains connection
- ▶ Housing made of impact-resistant plastic IK08
- ▶ Dimmable in four stages
- ▶ LED status indicator for the installed 4 Ah battery
- ▶ Integrated tilt protection protects the lens and housing from damage
- ▶ Support adjustable in angle
- ▶ Ergonomic handle for transport

	100%	75%	50%	25%
Light duration (approx. in hours)				
	0:45 h	0:45 h	1:25 h	3:10 h
<i>Technical data</i>				
Art. no.	LBS 10000 AC/DC 6903000			
Electrical connection	V/W	230 / 18 / 90		
Energy efficiency class		F		
Connection cable length	m	5		
Impact resistance		IK08		
Dimensions (L x W x H) approx.	mm	340x182x265		
Weight approx.	kg	3.2		



5700 K (daylight white)

Rechargeable battery operation Mains operation Dimmable IP 54

Scope of delivery:
Bosch battery adapter
Makita battery adapter
Milwaukee battery adapter
Metabo battery adapter
Mains cable 230V 5 m
Tripod 3m
Traverse for mounting a second construction spotlight



Accessory	Art. no.
Adapter DeWalt 18V	6909036
Festool 18V adapter	6909037
Adapter Einhell 18V	6909038

LBS 12500-3 AC/DC - LED construction spotlight with 360° beam angle

- ▶ Perfectly suited for the construction site or workshop for 360° lighting, e.g. for painting walls and ceilings or for drywall construction
- ▶ Compatible with 230 V mains connection or 18 V batteries* thanks to the battery adapter supplied
- ▶ Four brightness levels

- ▶ Integrated LED display for brightness levels
- ▶ Mobile thanks to attached carrying handles and an all-round cable winder
- ▶ Practical hanging hook on the underside of the lamp

Hybrid 230V and 18V rechargeable battery

100%	75%	50%	25%
Light duration with battery (approx. in hours)			
0:45 h	1:10 h	2:00 h	4:45 h

Technical data		LBS 12500-3 AC/DC
Art. no.		6903010
Electrical connection	V/W	18/230 / 100
Energy efficiency class		E
Connection cable length	m	5
Impact resistance		IK08
Dimensions (L x W x H) approx.	mm	280 x 286 x 360
Weight approx.	kg	4.3



6500 K (neutral white light)

Rechargeable battery operation | Mains operation | Dimmable | IP 54

Scope of delivery:
 Mains cable 230V 5 m
 Battery adapter (Bosch, Makita, Metabo, Milwaukee)

Accessories	Art. no.
3 m. Telescopic tripod with crossbar	6909000
Bracket for construction spotlights	6909001
Adapter	
Bosch Professional 18V	6909004
Makita 18V	6909005
Milwaukee / DeWalt 18V	6909006
Metabo 18V	6909007
Festool 18V	6909008
Fein 18V	6909009
Einhell 18V	6909010

LLS 23000-2 AC - LED light column with extendable telescopic spotlight

- ▶ Integrated pull-out spotlight on top of device, flexibly tiltable and swivelling with an output of 3000 lumens.
- ▶ Three brightness levels for optimal light adjustment and energy savings.
- ▶ Perfect for construction sites or workshops, providing 360° lighting, e.g. for painting walls or drywall installation.

- ▶ Mobile thanks to attached carrying handles, transport rollers and a cable reel around the perimeter.
- ▶ Built-in parking brake for a stable hold
- ▶ Two integrated sockets for consumers up to 3000 W power
- ▶ Integrated LED display for brightness levels


100% Spotlight	100% Main light	50% Main light	25% Main light
----------------	-----------------	----------------	----------------

Technical data		LLS 23000-2 AC
Art. no.		6904000
Electrical connection	V/W	230 / 30/200
Connection cable length	m	5
Energy efficiency class		E
Impact resistance		IK08
Dimensions (L x W x H) approx.	mm	525 x 430 x 1300
Weight approx.	kg	9.6



6500 K (neutral white light)

Mains operation | Dimmable | IP 54



▶ 360° lighting for construction site or workshop

Scope of delivery:
 Mains cable 230V 5 m
 Carrier bag

LBS 13500-3 AC – LED construction spotlight with tripod

- ▶ Construction spotlights for 360° lighting on construction sites
- ▶ Each spotlight individually adjustable for the right lighting position
- ▶ Four brightness levels per spotlight for optimal light adjustment and energy savings.

- ▶ Flexibly height-adjustable up to 2.2 m - adapts to any work situation
- ▶ Stable stand thanks to three sturdy feet – secure hold even on uneven surfaces

100%	75%	50%	25%
------	-----	-----	-----

Technical data		LBS 13500-3 AC
Art. no.		6903005
Electrical connection	V/W	230 / 100
Connection cable length	m	5
Energy efficiency class		D
Impact resistance		IK08
Dimensions (L x W x H) approx.	mm	258 x 210 x 1028
Weight approx.	kg	9



6500 K (neutral white light)

Mains operation | Dimmable | IP 54



▶ Fully foldable and weighing only approx. 9 kg for easy transport.

LTL 300 DC – Compact, powerful penlight with COB LED

- ▶ Robust aluminium housing
- ▶ Can be operated with 700 mAh rechargeable battery or 2 x AAA batteries
- ▶ Rechargeable via USB-C interface
- ▶ Practical clip for attaching to shirt or trouser pocket, also serves as roll protection
- ▶ Practical UV function for document verification or fluorescence examinations, for example
- ▶ Simple operation with end cap switch
- ▶ Equipped with battery charge indicator

100%	UV
Light duration (approx. in hours)	
1:30 h	1:00 h

Technical data		LTL 300 DC
Art. no.		6901005

Capacity	mAh	700
Beam angle	°	60
Light range max.	m	30
Service life	m	10000
Impact resistance		IK07
Dimensions (L x W x H) approx.	mm	158 x 16 x 20
Weight approx.	g	70



6500 – 7000 K

Rechargeable battery operation | Dimmable | USB TYPE C | IPX4



▶ Practical clip for attaching to a shirt or trouser pocket

Scope of delivery:
USB-C charging cable 0.8 m

LTL 1400 DC – Compact, powerful torch with COB LED for a wide range of applications

- ▶ Robust aluminium housing
- ▶ Can be operated with 2,000 mAh rechargeable battery or 4 x AAA batteries
- ▶ Rechargeable via USB-C interface
- ▶ Four practical lighting modes for every situation: Medium, High, Low, Strobe, SOS
- ▶ Equipped with battery charge indicator
- ▶ Integrated focus function

100%	40%	1.5%	Strobe	SOS
Light duration (approx. in hours)				
2:00 h	3:30 h	50:00 h	2:00 h	2:30 h

Technical data		LTL 1400 DC
Art. no.		6901000

Capacity	mAh	2,000
Beam angle	°	120
Light range max.	m	150
Service life	m	10000
Impact resistance		IK07
Dimensions (L x W x H) approx.	mm	175 x 28 x 38
Weight approx.	g	210



6000 K (daylight white)

Rechargeable battery operation | USB TYPE C | IPX4

Scope of delivery:
USB-C charging cable 0.8 m

LAL 1000 DC – Compact, powerful work lamp with COB and SMD LED for a wide range of applications

- ▶ Robust aluminium housing
- ▶ Can be operated with 1,000 mAh rechargeable battery or 3 x AAA batteries
- ▶ Rechargeable via USB-C interface
- ▶ Three practical lighting modes for every situation: High, Medium, Low
- ▶ Integrated spotlight on the top of the lamp
- ▶ Equipped with battery charge indicator
- ▶ Equipped with distance sensor on the front of the device to automatically switch off the light source
- ▶ Integrated magnetic holder

100%	50%	25%	Spotlight
Light duration (approx. in hours)			
1:30 h	3:00 h	5:00 h	6:00 h

Technical data		LAL 1000 DC
Art. no.		6901010

Capacity	mAh	1,000
Beam angle	°	65
Light range max.	m	55
Service life	m	10000
Impact resistance		IK07
Dimensions (L x W x H) approx.	mm	121 x 44 x 26
Weight approx.	g	140



7500 K (cool daylight)

Rechargeable battery operation | Dimmable | USB TYPE C | IPX4



▶ Practical clip for attaching to a shirt or trouser pocket

Scope of delivery:
USB-C charging cable 0.8 m

3-in-1 LTL 350-3 DC - 3-in-1 LED torch for a bunch of different uses

▶ Lamp body with three different attachments

	High	Low
Light duration (approx. in hours)		
Torch	2:00 h	4:30 h
Flexible lamp	5:00 h	8:00 h
Work lamp	1:30 h	4:00 h
Technical data		
Art. no.	3-in-1 LTL 350-3 DC 6901013	
Capacity	mAh	4,000
Beam angle	°	70
Light range max.		
Torch	m	100
Flexible lamp	m	154
Work lamp	m	25
Service life	m	10000
Impact resistance		IK07
Dimensions (L x W x H) approx.	mm	191 x 557 x 351
Weight approx.	g	80

- ▶ Operation with 2200 mAh battery
- ▶ Rechargeable via USB-C interface
- ▶ Lamp head can be changed quickly thanks to quick-release mechanism
- ▶ With torch, swivelling and flexible attachment
- ▶ Two practical lighting modes: Low, High
- ▶ Integrated focus function
- ▶ Equipped with battery charge indicator
- ▶ Magnetic holder on underside of lamp
- ▶ Robust aluminium housing

250 lumen



350 lumen

180 lumen



7500 K (cool daylight)



Scope of delivery:
 USB-C charging cable 0.8 m
 Attachment with flexible lamp
 Attachment with torch
 Attachment with work lamp

LSL 500 DC – Compact, powerful headlamp with COB and SMD LED for wide-angle and spot lighting

- ▶ Robust plastic housing
- ▶ Can be operated with 1000 mAh rechargeable battery or 3 x AAA batteries
- ▶ Rechargeable via USB-C interface
- ▶ Four practical lighting modes for every situation
- ▶ Weatherproof thanks to IP54

- ▶ Equipped with battery charge indicator
- ▶ Stepless swivelling lamp head
- ▶ Integrated sensor mode; switch off the lamp by waving your hand in front of it.
- ▶ Lamp can also be found in the dark thanks to fluorescent components
- ▶ Memory function for saving the selected light mode

SMD: High	SMD: Low	COB on	COB and SMD on
Light duration (approx. in hours)			
2:00 h	10:00 h	4:00 h	1:30 h
Technical data			
Art. no.	LSL 500 DC 6905000		
Capacity	mAh	1,000	
Beam angle	°	85	
Light range max.	m	80	
Service life	m	10000	
Impact resistance		IK07	
Dimensions (L x W x H) approx.	mm	68 x 39 x 73	
Weight approx.	g	90	



500 lumen



7000 K (neutral white light)



▶ Lamp can also be used without headband thanks to magnetic mount on rear

Scope of delivery:
 USB-C charging cable 0.8 m

LML 1200 DC - Extendable motor compartment light with SMD LED

- ▶ Robust aluminium - plastic housing
- ▶ 360° rotating hook for mounting on the bonnet or in the vehicle interior
- ▶ Extendable up to 1870 mm
- ▶ Two practical lighting modes: Low, High
- ▶ Equipped with battery charge indicator
- ▶ Rubber-coated hooks protect the bodywork from damage

High	Low	
Light duration (approx. in hours)		
2:00 h	6:00 h	
Technical data		
Art. no.	LML 1200 DC 6906000	
Capacity	mAh	4,000
Beam angle	°	70
Light range max.	m	40
Service life	m	10000
Impact resistance		IK07
Dimensions (L x W x H) approx.	mm	1214 x 130 x 77
Weight approx.	kg	1.1



1200 lumen



6500 K (neutral white light)



- Operation with 4000 mAh battery
- Rechargeable via USB-C interface

Scope of delivery:
 USB-C charging cable 2 m

